

# SPENT NUCLEAR FUEL STORAGE

## BASIC CONCEPT

### Eletronuclear Policy

“Almirante Álvaro Alberto Nuclear Power Plant shall own sufficient storage capacity for the total amount of spent fuel elements generated during the life time of the units 1, 2 and 3 (60 years), comprising the storage pools of the units and a specific external store to be constructed in the Power Plant area.”

# ANGRA 1+2 → OPERATIONAL REQUIREMENTS

## Storage Capacity of the Internal Pools


Angra	Storage capacity of the internal pools (assemblies)	Number of assemblies into the reactor core (assemblies)	End of storage capacity of the internal pools (year)
1	1252	121	2020
2	1084	193	2018

# SPENT FUEL COMPLEMENTARY STORAGE UNIT - CNAAA

## Brazil - Responsibilities

ELETRONUCLEAR  
ETN

COMISSÃO NACIONAL DE ENERGIA NUCLEAR  
CNEN




# SPENT FUEL COMPLEMENTARY STORAGE UNIT - CNAAA

## ELETRONUCLEAR Strategy

CENTRAL NUCLEAR ALMIRANTE ÁLVARO  
 ALBERTO NUCLEAR - CNAAA  
 INITIAL STORAGE

DICOMBUS - CNEN  
 LONG TERM STORAGE  
 COMPLEX




# SPENT FUEL COMPLEMENTARY STORAGE UNIT - CNAAA

## ELETRONUCLEAR Strategy

CENTRAL NUCLEAR ALMIRANTE ÁLVARO  
ALBERTO NUCLEAR - CNAAA  
INITIAL STORAGE

DICOMBUS - CNEN  
LONG TERM STORAGE  
COMPLEX



# SPENT FUEL COMPLEMENTARY STORAGE UNIT - CNAAA Conceptual Design

- The Spent Fuel Complementary Storage Unit will be composed of wet storage tanks, with similar conception and design of the power plants spent fuel pools;
- The Unit is being designed with two modules to be implemented in phases of construction;
- The first module will be operating in 2018, and will have a storage capacity of 2,400 fuel assemblies. The second module should have a storage capacity of 2,400 fuel assemblies;
- The heat loads are:


NPP	Unit Heat (kWt)	UFC 1		UFC 2		TOTAL	
		SFs (unit)	Heat (kWt)	SFs (unit)	Heat (kWt)	SFs (unit)	Heat (kWt)
Angra 1	0,99	900	891	1.200*	1.188*	2.100*	2.079*
Angra 2	1,25	1.500	1.875	1.200*	1.500*	2.700*	3.375*
Angra 3							
<b>TOTAL</b>		<b>2.400</b>	<b>2.766</b>	<b>2.400*</b>	<b>2.688*</b>	<b>4.800*</b>	<b>5.454*</b>

\* The values for UFC 2 should be confirmed during the planning of the 2nd construction phase.

# SPENT FUEL COMPLEMENTARY STORAGE UNIT - CNAAA Site Selection



# CONCEPTUAL DESIGN - Flow diagram







# CONCEPTUAL DESIGN - Layout

2<sup>a</sup> Phase of Constuction

1<sup>a</sup> Phase of Constuction



# CONCEPTUAL DESIGN - Layout




CORTE E-E


1ª Phase of Constuction

2ª Phase of Constuction

# CONCEPTUAL DESIGN - Layout




EL. +3,00 m



EL. +10,50 m

# CONCEPTUAL DESIGN - Layout



CORTE A-A